

CEN-PE-CO AUTOMATIC TRANSMISSION FLUID

A heavy duty automatic transmission fluid exceeding the requirements of both DEXRON® II and Ford MERCON® (pre-1992 version) specifications.

OUTSTANDING FEATURES AND BENEFITS:

100% pure paraffin base for exceptional heat resistance	Reduces wear
Compatible with all seal materials	Excellent rust and oxidation protection
	Extends transmission life

EXCEEDS SPECIFICATIONS:

DEXRON® II	Caterpillar TO-2
Ford MERCON® II (pre-1992)	Sunstrand Hydraulic Pump
Ford M2C138-CJ, M2C166-H	Denison Hydraulic
General Motors 6137	Sperry Vickers Hydraulic
Allison C-3, C-4	AGCO 411

CONTAINERS:

55 Gallon Drum	5 Gallon Pail
35 Gallon Drum	1 quart can (24 per case)
20 Gallon Drum	

TYPICAL CHARACTERISTICS:

Viscosity	
SUS @ 210° F.	50
SUS @ 100° F.	172
cSt @ 100° C.	7.3
cSt @ 40° C.	37
Viscosity Index	150
Flash Point	380° F.
Pour Point	-40° F.
Seal Compatibility (GM & Ford Methods)	Pass
Color	Red

Central Petroleum Company

11810 Madison Ave.
Cleveland, OH 44107-0597

201 East Lincoln Street
Walcott, IA 52773-0116

800-553-1891 FAX 563-284-5124



CEN-PE-CO AUTOMATIC TRANSMISSION FLUID

LIMITATIONS:

Cen-Pe-Co Automatic Transmission Fluid is not recommended for:

- Transmission calling for DEXRON® III
- Transmissions calling for MERCON V
- Post-1992 transmissions calling for MERCON®
- Applications at temperatures below -40° F.

Cen-Pe-Co Synthetic Blend ATF exceeds these specifications and is recommended in these applications.

Central Petroleum Company believes that most fluids designed to meet the cold temperature flow requirements of these newer specifications lack the film strength needed for heavy-duty applications. Cen-Pe-Co Automatic Transmission Fluid is superior for any application calling for DEXRON® II or pre-1992 MERCON®.