

CEN-PE-CO SYNTHETIC ATF

Cen-Pe-Co Synthetic ATF is a fully synthetic, premium quality, multi-vehicle automatic transmission fluid. It is recommended for automatic transmissions in most American, Asian, and European passenger vehicles, as well as a wide range of equipment from small cars to trucks and buses to heavy-duty off-road equipment

OUTSTANDING FEATURES AND BENEFITS:

Superior Wear Performance—Gears
Clutches, and Bearings
Synthetic Base Oil
Superior Heat Resistance

Superior Low Temperature Performance
Improved Shear Stability
Longer Service Life

RECOMMENDED IN THE FOLLOWING APPLICATIONS:

Aisin Warner AW1*, JWS 3309

Allison C-4, TES-295 (TranSynd®), TES-389

Audi G-052-025-A2, G-052-162-A1, G 052
990, G055 005*, G055 162*

BMW LA2634, LT71141, 7045E, LA 2634,
LT 71141, 83 22 0 142 516*

Chrysler ATF+4, ATF+3, ATF+2, ATF+

Ford MERCON® V, MERCON® SP*,
MERCON® LV*, MERCON®, FNR5

GM DEXRON® VI*, DEXRON® III,
DEXRON® II, DEXRON®

Honda ATF-Z1, DW1*

Hyundai SP II, SP III, SP IV*, SPH IV*, SP
IV RR*, SP4 M*, JWS 3314, JWS 3317, NWS
9638

JATCO Idemitsu K17

Kia SP II, SP III, SP IV*, SPH IV*, SP IV
RR*, SP4 M*, JWS 3314, JWS 3317, Red 1

Mazda F1, ATF M III, ATF MV, ATF FZ*

Mercedes Benz 236.1, 236.2, 236.3, 236.5,
236.6, 236.7, 236.9, 236.10, 236.11, 236.81,
236.12*, 236.14*, 236.15*, 236.41*

Mitsubishi ATF J2, ATF J3*, ATF PA*, SP-
III, SP-II

Mopar AS68RC

Nissan 402, Matic K, Matic J, Matic D, Matic
S*, Matic W*

Saab 93 165 147*

Subaru ATF, ATF-HP

Suzuki 3314 3317

Toyota T-IV, T-III, WS*, JWS 3324*

Volvo 97340, 97341, 116162131256774*,
31256675*

VW G052 162, G052 540*, G052 990, G055
005*, G055 025, G055 162*

ZF S671 090 255*, TE-ML 03D, TE-ML 04D,
TE-ML 05L, TE-ML 09, TE-ML 14A, TE-ML
14B, TE-ML 16M, TE-ML 17C, TE-ML 20B,
TE-ML 21L

* Cen-Pe-Co Synthetic ATF is not thin enough to meet the viscosity requirements of this specification, but is recommended based on experience.

TranSynd is a registered trademark of Castrol and used under license by Allison. Mercon is a registered trademark of Ford. Dexron is a registered trademark of General Motors

Central Petroleum Company

11810 Madison Ave.
Cleveland, OH 44107-0597

201 East Lincoln Street
Walcott, IA 52773-0116

800-553-1891 FAX 563-284-5124



CEN-PE-CO SYNTHETIC ATF

NOT RECOMMENDED IN THE FOLLOWING APPLICATIONS:

Allison TES-353 (TranSynd RD)
Ford Type F
Mercedes Benz 236.12, 236.8, 236.16
Volvo 97342
ZF 1375.4
Continuously Variable Transmissions (CVT),
except the few hybrids calling for regular ATF
Dual Clutch Transmissions
Compressors*
Hydraulic pumps*

*Use Cen-Pe-Co Heavy Duty Automatic Transmission Fluid for those calling for Dexron II.

RECOMMENDED IN THE FOLLOWING TRANSFER CASE APPLICATIONS:

Ford MERCON® V, XL12
GM AutoTrak II
Mercedes GL450, 3403

RECOMMENDED IN THE FOLLOWING POWER STEERING APPLICATIONS:

Chrysler MS-1872, MS-5931, 04883077, MS 9602, MS-10838, 05142893AA
Ford M2C195-A
GM 89021184, 1052884 (GM 9985010), 12345866 (GM 9985835)
Hyundia/KIA PSF-3
Mercedes-Benz 236.3 (000 989 88 03)
Mitsubishi PS fluid, Diamond SP-III
Nissan PSF-II
Saab 45 30 09 800
Subaru K0209A0080
Toyota PSF Type EH 008886-01
ZF TE-ML 09

TYPICAL CHARACTERISTICS:

Viscosity	7.5 cSt @ 100° C. 40 cSt @ 40° C.
Viscosity Index	157
Pour Point (°F)	-44
Specific Gravity	0.85
Color	Red